

FLITE® Waterproof, Lightweight, Comfortable and Safe



Lightweight upper, cushioned heel, slip-resistant nitrile rubber outsole and ASTM composite toe.

FLITE® Mid-Calf Safety Toe Boot is a Revolution in Protective Footwear

Made from Aerex 1.5.5® – a proprietary, chemical-resistant, thermally-insulative, microcellular polymer, resulting in boots that are over 40% lighter compared to most steel toe PVC and rubber knee boots. Lightweight upper, cushioned heel, slip-resistant nitrile rubber outsole and composite toe provide superior comfort and safety.

- 10-inch height with composite safety toe and red Chevron-Plus® outsole.
- Slip resistant per ASTM F3445, the standard specification as of July 2022.
- Thumb pocket at top opening for firm, no-slip grip for easy donning.
- Beveled heel for reduced back and leg strain.
- Composite safety toe meets ASTM F2413 M/1/C EH* and will not set off metal detectors.
- Chevron-Plus® nitrile rubber outsole provides superior grip on dry, wet and contaminated surfaces.
- Durable, seamless upper is 100% liquidproof.
- Tiny air bubbles in the material keep feet warm in cold and cool in heat.
- Calf-Relief Topline™ (CRT) for easier on and off and roomier calf space.
- Tread wear indicators to show when half the tread has worn away
- Achieved a passing result for ASTM F1671 resistance to viral penetration.



Chevron-Plus® Outsole:
Provides superior grip on dry, wet and contaminated surfaces.

FLITE® MID-CALF BOOT		
■ 26226	Blue Upper – Red Chevron-Plus Outsole - Ht. 10" – Composite Safety Toe – EH Rated	4 – 15

 WATERPROOF	 LIGHTWEIGHT	 INSULATING	 SAFETY TOE
 CHEMICAL RESISTANT	 OIL RESISTANT	 SLIP RESISTANT	 ELECTRICAL HAZARD

Ideal Applications: Warehouses, Work Shops, Construction, Transportation, Municipalities, Janitorial, and a wide array of Food Processing (Dairy, Meats, Vegetables, and Breweries).

Chemical Resistance: Superior chemical resistance to fats, oils, hydrocarbons, and many acids and alkalis.



*Boot shall withstand 18,000 volts at 60 HZ for 1 minute with no current flow or leakage current in excess of 1.0 milliamperes under dry conditions tested as per lab conditions in Test Method F2412.

Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts, or apparatus. Electric Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive footwear is required.

01/23

TINGLEY

est. 1896

ISO 9001 Certified
www.tingleyrubber.com
 1•800•631•5498

