

Impact, Oil, Water, Cut, and Flame Resistant Goatskin Gloves

DESCRIPTION

This premium-grade grain goatskin leather drivers glove is an outstanding cut-resistant option that features a thin Aralene® (enhanced aramid fiber) shell sewn-in plus soft, TPR impact protection added to the back of the hand. The leather is further enhanced by being both oil and water-resistant.

Each pair is individually packaged in a polybag.



INDUSTRY

Oil and Gas	Material Handling	Manufacturing
Lumber		Farming
Construction	Sheet Metal Work	Fabrication
Masonry		

FEATURES

- Premium-grade grain goatskin offers ultimate dexterity
- Proprietary oil/water resistant manufacturing process to ensure longer lasting benefits over a spray-on treatment
- Thin Aralene® (enhanced aramid fiber) liner is sewn into the glove and offers great dexterity, cut resistance, and heat resistance
- Soft, flexible, TPR impact protection over the fingers and metacarpal bones provides tough protection
- Sewn with aramid fiber for added durability and cut and heat resistance
- Ergonomic keystone thumb improves durability, comfort, and dexterity while reducing hand fatigue
- Overcast color on hem for easy size identification
- Open cuff allows for easy donning and removal

SPECIFICATIONS

SHELL		SHELL COLOR	GRADE	LINER	LINER COLOR	THUMB	CUFF	IMPACT PROTECTION	IMPACT	CUT	ASTM F2992-15 RESULTS	
Grain Goatskin		Brown	Premium	Aralene®	Yellow	Keystone	Open	TPR		Level 2	Level A5	2,558 Grams
ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS	EN 407 LEVELS	ASTM F2675 TESTED	ARC RATING (ATPV)	HEAT ATTENUATION FACTOR (HAF)	NFPA 70E ARC-FLASH PPE CATEGORY				
Level 4	Level 4	140 Newtons	3X23EP	X2XXXX	Yes	50 Cal/cm²	95%	4				

ITEM CIA3800 SIZES 7(S)-11(2XL)

- EN 388 Levels: 3X23EP
- EN 407 Levels: X2XXXX

Meets ANSI/ISEA 105-2016 standard

- Cut Level A5
- ASTM F2992-15 Results = 2,558 grams
- Abrasion Level 4
- Puncture Level 4
- Puncture Results: 140 Newtons

Meets ANSI/ISEA 138-2019 standard

- Impact Level (Overall): 2
- Impact Level (Knuckles): 2
- Impact Level (Fingers/Thumb): 2



PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	N/A	N/A	N/A	N/A	N/A
INNER PACK UPC	12/PACK	816368028125	816368028132	816368028149	816368028156	816368028163
CASE GTIN	6 PK/CASE	10816368028122	10816368028139	10816368028146	10816368028153	10816368028160
CASE WEIGHT (IN POUNDS)		48	48	48	43.2	48
OVERCAST COLOR		Red	Green	Brown	Blue	Yellow

Tested to ASTM F2675

Arc Rating (ATPV) = 50 Cal/cm²

Heat Attenuation Factor (HAF) = 95%

NFPA 70E Arc-Flash PPE Category: 4

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

Global Glove
& Safety Manufacturing, Inc.

