

Cut, Abrasion, and Puncture Resistant Grain Goatskin Gloves

DESCRIPTION

This standard-grade grain goatskin leather drivers glove is an outstanding cut-resistant option that features a thin Aralene® (enhanced aramid fiber) liner sewn-in. Each pair is individually packaged in a polybag.

INDUSTRY

Lumber	Sheet Metal Work
Construction	Manufacturing
Masonry	Farming
Material Handling	Fabrication



FEATURES

- Standard-grade grain goatskin offers ultimate dexterity
- Thin Aralene® (enhanced aramid fiber) liner is sewn into the glove and offers great dexterity, cut resistance, and heat resistance
- Ergonomic keystone thumb improves durability, comfort, and dexterity while reducing hand fatigue
- Sewn with aramid fiber for added durability and cut and heat resistance
- Overcast color on hem for easy size identification
- Open cuff allows for easy donning and removal

ITEM CR3900

SIZES 7(S)-11(2XL)

- EN 388 Levels: 3X23E
- EN 407 Levels: X2XXXX

Meets ANSI/ISEA 105-2016 standard

- Cut Level A5
- ASTM F2992-15 Results = 2,604 grams
- Abrasion Level 4
- Puncture Level 4
- Puncture Results: 104 Newtons



SPECIFICATIONS

SHELL	COLOR	LINER	STITCHING	THUMB	CUFF		
Grain Goatskin	White	Aralene®	Sewn With Aramid Fiber	Keystone	Open		
CUT	ASTM F2992-15 RESULTS		ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS	EN 407 LEVELS
Level A5	2,604 Grams		Level 4	Level 4	104 Newtons	3X23E	X2XXXX

PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	NA	NA	NA	NA	NA
INNER PACK UPC	12/PACK	816368028859	816368028866	816368028873	816368028880	816368028897
CASE GTIN	6 PK/CASE	10816368028856	10816368028863	10816368028870	10816368028887	10816368028894
CASE WEIGHT (IN POUNDS)		21.3	23.3	24.4	25.3	26.8
OVERCAST COLOR		Red	Green	Brown	Blue	Yellow

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com


Global Glove
& Safety Manufacturing, Inc.