Foggers

Electro-Gen Thermal Fogger

For powerful, versatile fogging. As a thermal fogger, this unit produces extremely fine particle size that mimics the behavior of smoke, delivering odor control deep into cracks, crevices and cavities. Use with <u>ODORx Thermo-55</u> solvent-based formulations. Or, detach the heater barrel for use as a cold sprayer with water-based products or ProRestore's <u>Disinfectant Spray Plus</u> antimicrobial products. Always follow fogging product label instructions exactly.

Features

- Produces a true "dry fog" with a very small particle size similar to smoke for deep penetration.
- Virtually eliminates the drips and streaks associated with conventional misters and foggers.
- Can be used as an electric sprayer to apply solvent- or water-based chemicals for deodorizing. Simply remove the heater barrel for this function.

Specifications

- Output spraying: 1 oz. (30 ml) per minute
- Output fogging: 1,000 cu. ft. (28 cu. m.) per minute
- Fogging: Hot: 13.5 microns
- Cold: 115 microns
- **Amps**: 8A (230V = 4 amps)
- Volts: 115V
- **Power**: 900W
- Motor: Electro-mechanical vibrator operating at 7,200 strokes per minute
- Pump: Displacement type
- Heating element : Thermostatically controlled
- Solution reservoir: Spun aluminum 3 qt. / 2.8 L capacity
- Operating temperature: 450°F–525°F | 232°C–274°C

Sizes • Options

- 116257 (102257000): One 110V unit
- 101277000: One 220V unit