# MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communicati Standard 29 CFR 1910.1200. Standard must be consulted specific requirements.		HMIS HAZARD RATING					
	HEAL	TH	1	(	) = INSIGNIFICANT	3 = HIGH	
	FLAM	IMABILITY	0	1	I = SLIGHT	4 = EXTREME	
		TIVITY	0	2	2 = MODERATE		
SAFETEC OF AMERIC	`A	TRANSPORTATION INFORMATION			FORMATION		
	PROF	PER SHIPPING	NAME	Not Regulated			
		RD CLASS / F		None / None	REF.	Not Applicable	
		TIFICATION N		None	LABI	EL None Required	
SECTION 1 - PRODUCT / COMPANY IDENTIFICATION							
IDENTITY (AS USED ON LABEL AND LIST)						Page 1 of 2	
SaniZide Plus™ Germicidal Solution							
MANUFACTURER'S NAME				EMERGENCY TEI	LEPHONE NUMBER	(24 Hours)	
Safetec of America, Inc.				(800) 255-3924	1		
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION			ATION		
887 Kensington Avenue @ William L. Gaite	r Pkwy.			(716) 895-1822	2		
(CITY, STATE AND ZIP CODE)	-			DATE PREPARED	) Septemb	per 1, 2004	
Buffalo, NY 14215		SUPERSEDES March 6, 2002			2002		
<b>SECTION 2 - HAZARDOUS INGRE</b>	DIENTS	/ IDENTI	ΓΥ INFO	RMATION			
HAZARDOUS COMPONENTS	CAS#	% (wt.) ACGIH TLV/TWA/STEL					
(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))		(OPTIONAL)	PPM			MG/M <sup>3</sup>	
Alkyl-dimethyl-benzyl-ammonium chloride 683	391-01-5	0.105	Nor	ne Established	None	Established	
Alkyl-dimethyl-ethyl benzyl- ammonium chloride 689	956-79-6	0.105	None Established None Est		Established		

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA	1			
ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES			
INHALATION: Brief (minutes) inhalation will not cause adverse effects, although, constant inhalation may cause irritation to upper respiratory tract.	Remove to fresh air; provide oxygen if breathing is difficult; seek medical attention if required.			
EYES: Brief contact to liquid or vapors may cause moderate irritation; prolonged contact may cause severe irritation associated with burning and redness.	Flush eyes with clear running water for a minimum of 25 minutes while holding eyelids open; if irritation persists, seek medical attention.			
INGESTION: Ingestion of this product may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	DO NOT induce vomiting; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.			
SKIN: Prolonged contact with skin may cause skin irritation.	Wash contaminated skin with mild soap and water; if irritation occurs and persists, seek medical attention.			
HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects have been established.	are possible irritation and discomfort; no known chronic effects			
CARCINOGENICITY NTP? No	IARC MONOGRAPHS? No OSHA REGULATED? No			
No additional information				
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY Exaggravated through prolonged exposure.	XPOSURE: Preexisting skin disorders may become			

#### MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

SaniZide Plus™ Germicidal Solution

Page 2 of 2

Date: September 1, 2004

## **SECTION 4 - FIRE FIGHTING MEASURES**

FLASH POINT (METHOD USED)

200°F (SETA)

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: Not Applicable

UEL: Not Applicable

**EXTINGUISHING MEDIA** 

Carbon dioxide (CO<sub>2</sub>), water, dry chemicals, synthetic foam. Type BC or ABC extinguishers.

#### SPECIAL FIRE FIGHTING PROCEDURES

Use self-contained breathing apparatus for maximum respiratory protection. Use water spray to cool fire-exposed containers and structures.

#### UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Vapors can be heavier than air. Strong acids and bases react with aluminum to form hydrogen which is explosive if ignited.

## SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

## STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

Provide adequate ventilation. Spills should be collected with approved inert absorbent for disposal. Use suitable disposal containers. Material collected with absorbent may be disposed of in a permitted landfill. Report per regulatory requirements.

## WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container(s) tightly closed when not in use. Store in cool, dry, ventilated area away from possible sources of ignition. The recommended storage temperature is between 50 and 120°F. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
RESPIRATORY PROTECTION	VENTILATION	LOCAL EXHAUST:	Recommended	
Ordinarily, none required		MECHANICAL (GENERAL):	Not required	
PROTECTIVE GLOVES	EYE PROTECTION		_	
Use impervious gloves to prevent prolonged contact.	Safety glasses recommended.			
OTHER PROTECTIVE CLOTHING OR EQUIPMENT	WORK / HYGIENIC F	PRACTICES	_	
Ordinarily, none required	Practice safe work habits. Use according to label instructions.			
SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES				
BOILING POINT	SPECIFIC GRAVITY	(WATER=1)		

SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES			
BOILING POINT	SPECIFIC GRAVITY (WATER=1)		
200°F	1.01		
VAPOR PRESSURE (mm Hg)	MELTING POINT		
Not determined	−1.1 °C		
VAPOR DENSITY (AIR=1)	PH		
>1	11 – 12		
SOLUBILITY IN WATER	EVAPORATION RATE (n-BUTYL ACETATE=1)		
Complete	Slower than ethyl ether		
APPEARANCE AND ODOR	RVOC, U.S. EPA (%)		
Clear liquid	0		

#### **SECTION 8 - STABILITY AND REACTIVITY**

0_0110110			
STABILITY	UNSTABLE:	CONDITIONS TO AVOID	
	STABLE: XXX	Extreme temperatures	

## INCOMPATIBILITIES (MATERIALS TO AVOID)

Strong oxidizers; anionic materials

#### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Decomposition will not occur if handled/stored properly. Thermal decomposition may emit nitrous oxides, ammoniacal vapors.

HAZARDOUS POLYMERIZATION	MAY OCCUR:		CONDITIONS TO AVOID
WILL	NOT OCCUR:	XXX	None known

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.